



InLei® & Light Lashes®
Via Nicolò Rezzara 15, 24020 Ranica (BG) | ITALIA
Cod. Fiscale e P.IVA IT04215490162
Tel. +39 035 511355 | Email: info@selitasrl.com

InLei® LASH FIX 2 - Lash Fixing
Revision nr. 1
Dated 24/10/2025
First compilation
Printed on 24/10/2025)

Safety Data Sheet

Complies with Annex II of REACH - Regulation (EU) 2020/878

Information Sheet for finished cosmetic products

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **InLei® LASH FIX 2 - Lash Fixing**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **not available**

1.3. Details of the supplier of the safety data sheet

Name: **SELITA SRL**
Full address: **via Nicolò Rezzara, 15**
District and Country: **24020 Ranica (Bergamo)**
Italia

Contacts: **Tel. +39035511355**
Cell. +393895618546

e-mail address: **info@selitasrl.com**

1.4. Emergency telephone number

For urgent information, please contact

+39 035 511355/+39 389 5618546 (Mon-Fri 9:00-18:00). Provides initial technical support. National Poisons Information Center (UK): 0344 892 0111 for healthcare professionals only Vergiftungsinformationszentrale (VIZ) (Austria): +43 1 406 43 43 National Poisons Information Center (Ireland): +353 (0)1 809 2566 (for professionals) or +353 (0)1 809 2166 (public) Italian National Institute of Health (ISS) – (Italy): +39 0382 24444 (Pavia); +39 06 3054343 (Rome) Swedish Poisons Information Center (Sweden): +46 10 456 6750 French Poison and toxicovigilance (France): + 33 3 83 85 21 92

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is a cosmetic product and as such is not subject to the obligation of having a safety data sheet in accordance with the REACH Regulation and being classified in accordance to the CLP Regulation.

Hazard classification and indication: --

2.2. Label elements

The product is exempt from the labelling obligation in accordance with the CLP Regulation.

Hazard pictograms: --

Signal words: --

Hazard statements: --

Precautionary statements: --

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Alcohols, -C16-18		
INCI CETEARYL ALCOHOL		
INDEX -	$6 \leq x < 7$	Aquatic Chronic 3 H412
EC 267-008-6		
CAS 67762-27-0		
REACH Reg. 01-2120092297-47-xxxx		
Alcohols, C16-18, ethoxylated		
INCI CETEARETH-20, CETEARETH-30, CETARETH-12, CETEARETH -25, CETEARETH-2		
INDEX -	$2,5 \leq x < 3$	Eye Irrit. 2 H319, Aquatic Chronic 3 H412
EC 500-212-8		
CAS 68439-49-6		
Dodecan-1-ol		
INCI LAURYL ALCOHOL		
INDEX -	$1,5 \leq x < 2$	Eye Irrit. 2 H319, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411
EC 203-982-0		
CAS 112-53-8		
REACH Reg. 01-2119787279-18-xxxx		
HYDROGEN PEROXIDE SOLUTION		
INCI HYDROGEN PEROXIDE		
INDEX 008-003-00-9	$1,5 \leq x < 2$	Ox. Liq. 1 H271, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: B
EC 231-765-0		Ox. Liq. 1 H271: $\geq 70\%$, Ox. Liq. 2 H272: $\geq 50\% - < 70\%$, Skin Corr. 1A H314: $\geq 70\%$, Skin Corr. 1B H314: $\geq 50\% - < 70\%$, Skin Corr. 1C H314: $\geq 50\% - < 70\%$, Skin Irrit. 2 H315: $\geq 35\% - < 50\%$, Eye Dam. 1 H318: $\geq 8\%$, Eye Irrit. 2 H319: $\geq 5\% - < 8\%$, STOT SE 3 H335: $\geq 35\%$
CAS 7722-84-1		LD50 Oral: 417,55 mg/kg, ATE Inhalation vapours: 11 mg/l
REACH Reg. 01-2119485845-22-XXXX		
Tetradecanol		
INCI MYRISTYL ALCOHOL		
INDEX -	$0,4045 \leq x < 0,4545$	Eye Irrit. 2 H319, Aquatic Chronic 1 H410 M=1
EC 204-000-3		
CAS 112-72-1		
REACH Reg. 01-2119485910-33-xxxx		
PHOSPHORIC ACID		
INDEX 015-011-00-6	$0 < x < 0,05$	Met. Corr. 1 H290, Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B
EC 231-633-2		Met. Corr. 1 H290: $\geq 20\%$, Skin Corr. 1B H314: $\geq 25\%$, Skin Irrit. 2 H315: $\geq 10\% - < 25\%$, Eye Dam. 1 H318: $\geq 25\%$, Eye Irrit. 2 H319: $\geq 10\% - < 25\%$
CAS 7664-38-2		LD50 Oral: 1530 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Wash immediately and thoroughly with running water. Get medical advice if you feel symptoms.

SKIN: Wash with plenty of water. Get medical advice if you feel symptoms.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice.

INHALATION: Remove to open air. Get medical advice if you feel symptoms.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία``»
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr. 2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de implementatie vanRichtlijn 2022/431
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	ACGIH	ACGIH 2025

HYDROGEN PEROXIDE SOLUTION

Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	0,71	0,5	0,71	0,5
MAK	DEU	0,71	0,5	0,71	0,5
VLA	ESP	1,4	1		
VLEP	FRA	1,5	1		
TLV	GRC	1,4	1	3	

TGG	NLD	1								
NDS/NDSch	POL	0,4	0,8							
WEL	GBR	1,4	1	2,8	2					
ACGIH		1,4	1							
Predicted no-effect concentration - PNEC										
Normal value in fresh water				0,01			mg/l			
Normal value in marine water				0,01			mg/l			
Normal value for fresh water sediment				0,04			mg/kg/d			
Normal value for marine water sediment				0,04			mg/kg/d			
Normal value of STP microorganisms				4,66			mg/l			
Health - Derived no-effect level - DNEL / DMEL										
	Effects on consumers				Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic		
Inhalation	1.39 ma/m3		0.21 ma/m3		3 ma/m3		1.4 ma/m3			

PHOSPHORIC ACID

Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2		4		INHAL
MAK	DEU	2		4		INHAL
VLA	ESP	1		2		
VLEP	FRA	1	0,2	2	0,5	
TLV	GRC	1		3		
VLEP	ITA	1		2		
TGG	NLD	1		2		
NDS/NDSch	POL	1		2		
WEL	GBR	1		2		
OEL	EU	1		2		
ACGIH		1		3		

Dodecan-1-ol

Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,001	mg/l			
Normal value for fresh water sediment				0,666	mg/kg			
Normal value for marine water sediment				0,067	mg/kg			
Normal value for the terrestrial compartment				0,132	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	
Oral				44,5 mg/kg bw/d				
Inhalation				77 mg/m3		220 mg/m3		313 mg/m3
Skin		75 mg/kg/d		44,5 mg/kg bw/d		125 mg/kg bw/d		89 mg/kg/d

Tetradecanol

Predicted no-effect concentration - PNEC								
Normal value in fresh water			0,00032	mg/l				
Normal value in marine water			0,000032	mg/l				
Normal value for fresh water sediment			0,36	mg/kg				
Normal value for marine water sediment			0,036	mg/kg				
Normal value of STP microorganisms			0,36	mg/l				
Health - Derived no-effect level - DNEL / DMEL								
			Effects on consumers				Effects on workers	
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic

	systemic	systemic	systemic
Inhalation		220 mg/m3	220 mg/m3
Skin		125 mg/kg bw/d	125 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

Ensure good ventilation in the workplace; do not drink, smoke and eat during use.

HAND PROTECTION
None required.

EYE PROTECTION
None required.

SECTION 9. Physical and chemical properties

Properties	Value	Information
Appearance	cream	
Colour	white	
Odour	characteristic	
Flash point	> 60 °C	
pH	2,5 - 3,5	
Density and/or relative density	0,95 - 1,00	

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

HYDROGEN PEROXIDE SOLUTION

Decomposes if exposed to: light, heat. Decomposes on contact with: alkaline metals. Possibility of explosion.

PHOSPHORIC ACID

Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

PHOSPHORIC ACID

Risk of explosion on contact with: nitromethane. May react dangerously with: alkalis, sodium borohydride.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

HYDROGEN PEROXIDE SOLUTION

Avoid exposure to: light, heat. Avoid contact with: alkaline substances.

10.5. Incompatible materials

HYDROGEN PEROXIDE SOLUTION

Incompatible with: flammable substances, acetone, ethanol, glycerol, organic sulphides, hydrated bases, oxidising substances, iron, copper, bronze, chromium, zinc, lead, silver, manganese, acetic acid.

PHOSPHORIC ACID

Incompatible with: metals, strong alkalis, aldehydes, organic sulphides, peroxides.

10.6. Hazardous decomposition products

PHOSPHORIC ACID

May develop: phosphoryl oxides.

SECTION 11. Toxicological information

ACUTE TOXICITY

Dodecan-1-ol

LD50 (Dermal):

> 2000 mg/kg coniglio

LD50 (Oral):

26530 mg/kg ratto

HYDROGEN PEROXIDE SOLUTION

LD50 (Oral):

1193 mg/kg Rat
at the concentration of 35%

LC50 (Inhalation vapours):

> 16,1 mg/l/4h Rat
at the concentration of 50%

ATE (Inhalation vapours):

11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Tetradecanol

LD50 (Dermal):

8000 mg/kg coniglio

LD50 (Oral):

> 2000 mg/kg ratto

LC50 (Inhalation vapours):

> 1,5 mg/l/1h ratto

PHOSPHORIC ACID

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Dodecan-1-ol

LC50 - for Fish

1,01 mg/l/96h

EC50 - for Crustacea

320 mg/l/48h daphnia magna

EC50 - for Algae / Aquatic Plants

0,33 mg/l/72h

Chronic NOEC for Fish

0,26 mg/l

Chronic NOEC for Crustacea

0,316 mg/l

HYDROGEN PEROXIDE SOLUTION

LC50 - for Fish	16,4 mg/l/96h
EC50 - for Crustacea	2,4 mg/l/48h
EC50 - for Algae / Aquatic Plants	1,38 mg/l/72h
Chronic NOEC for Crustacea	0,63 mg/l

Tetradecanol

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	3,2 mg/l/48h daphnia
EC50 - for Algae / Aquatic Plants	> 10 mg/l/72h

12.2. Persistence and degradability

Dodecan-1-ol

Rapidly degradable

HYDROGEN PEROXIDE SOLUTION

Solubility in water	100000 mg/l
Rapidly degradable	

Tetradecanol

Rapidly degradable

PHOSPHORIC ACID

Solubility in water	> 850000 mg/l
Degradability: information not available	

12.3. Bioaccumulative potential

HYDROGEN PEROXIDE SOLUTION

Partition coefficient: n-octanol/water	-1,57
--	-------

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety

regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Ox. Liq. 1	Oxidising liquid, category 1
Ox. Liq. 2	Oxidising liquid, category 2
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H271	May cause fire or explosion; strong oxidiser.
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

Note for users:

The information contained in this document are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.