



InLei® & Light Lashes®
Via Nicolò Rezzara 15, 24020 Ranica (BG) | ITALIA
Cod. Fiscale e P.IVA IT04215490162
Tel. +39 035 511355 | Email: info@selitasrl.com

InLei® LASH MOLECULAR 4 - Molecular reconstruction for eyelashes and eyebrows
Revision nr. 1
Dated 31/10/2025
First compilation
Printed on 31/10/2025

Safety Data Sheet

Complies with Annex II of REACH - Regulation (EU) 2020/878

Information Sheet for finished cosmetic products

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **InLei® LASH MOLECULAR 4 - Molecular reconstruction for eyelashes and eyebrows**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **not available**

1.3. Details of the supplier of the safety data sheet

Name: **SELITA SRL**
Full address: **via Nicolò Rezzara, 15**
District and Country: **24020 Ranica (Bergamo)**
Italia

Contacts: **Tel. +39035511355**
Cell. +393895618546

e-mail address: **info@selitasrl.com**

1.4. Emergency telephone number For urgent information, please contact

+39 035 511355/+39 389 5618546 (Mon-Fri 9:00-18:00). Provides initial technical support. National Poisons Information Center (UK): 0344 892 0111 for healthcare professionals only Vergiftungsinformationszentrale (VIZ) (Austria): +43 1 406 43 43 National Poisons Information Center (Ireland): +353 (0)1 809 2566 (for professionals) or +353 (0)1 809 2166 (public) Italian National Institute of Health (ISS) – (Italy): +39 0382 24444 (Pavia); +39 06 3054343 (Rome) Swedish Poisons Information Center (Sweden): +46 10 456 6750 French Poison and toxicovigilance (France): + 33 3 83 85 21 92

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is a cosmetic product and as such is not subject to the obligation of having a safety data sheet in accordance with the REACH Regulation and being classified in accordance to the CLP Regulation.
However, CLP hazard classification and labelling for physical hazards are reported here for correct product management.

Hazard classification and indication:
Flammable liquid, category 2 **H225** **Highly flammable liquid and vapour.**

2.2. Label elements

The product is exempt from the labelling obligation in accordance with the CLP Regulation. The directions on the label are optional.

Hazard pictograms:



Signal words:	Danger
Hazard statements:	
H225	Highly flammable liquid and vapour.
Precautionary statements:	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378	In case of fire: use . . . to extinguish.
P233	Keep container tightly closed.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hexamethyldisiloxane		
INCI DISILOXANE		
INDEX -	$3 \leq x < 3,5$	Flam. Liq. 2 H225, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411
EC 203-492-7		
CAS 107-46-0		
REACH Reg. 01-2119496108-31--XXXX		
Ethaniminium, N, N, N-trimethyl-2 - [[(2-methyl-1-oxo-2-propen-1-yl) oxy] -, chloride (1: 1), homopolymer		
INCI POLYQUATERNIUM-37		
INDEX -	$1,5 \leq x < 2$	Aquatic Chronic 2 H411
EC 607-876-9		
CAS 26161-33-1		
BENZENE		
INDEX 601-020-00-8	$0 < x < 0,05$	Flam. Liq. 2 H225, Carc. 1A H350, Muta. 1B H340, STOT RE 1 H372, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 200-753-7		
CAS 71-43-2		
TOLUENE		
INCI TOLUENE		
INDEX 601-021-00-3	$0 < x < 0,05$	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC 203-625-9		
CAS 108-88-3		
REACH Reg. 01-2119471310-51-XXXX		
METHANOL		
INDEX 603-001-00-X	$0 < x < 0,05$	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370 STOT SE 2 H371: $\geq 3\%$ - $< 10\%$ ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation vapours: 3 mg/l
EC 200-659-6		
CAS 67-56-1		
PHENOL		
INDEX 604-001-00-2	$0 < x < 0,05$	Muta. 2 H341, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318 Skin Corr. 1B H314: $\geq 3\%$, Skin Irrit. 2 H315: $\geq 1\%$ - $< 3\%$ LD50 Oral: 282 mg/kg, LD50 Dermal: 660 mg/kg, ATE Inhalation mists/powders: 0,501 mg/l
EC 203-632-7		
CAS 108-95-2		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Wash immediately and thoroughly with running water. Get medical advice if you feel symptoms.

SKIN: Wash with plenty of water. Get medical advice if you feel symptoms.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice.

INHALATION: Remove to open air. Get medical advice if you feel symptoms.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Wash hands after use.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Store the containers sealed, in a well ventilated place, away from direct sunlight.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei 2024, nr. 2024-0000092805, tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2022/431
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

BENZENE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	3,25	1			SKIN
VLEP	FRA	1,65	0,5			SKIN
TLV	GRC	1,65	0,5			SKIN
VLEP	ITA	0,66	0,2			SKIN
TGG	NLD	0,66	0,2			SKIN
NDS/NDSch	POL	0,66	0,2			SKIN
WEL	GBR	3,25	1			SKIN
OEL	EU	0,66	0,2			SKIN
ACGIH			0,02			SKIN

TOLUENE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	380	100	SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
TLV	GRC	192	50	384	100	
VLEP	ITA	192	50	384	100	SKIN
TGG	NLD	150		384		
NDS/NDSch	POL	100		200		SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
ACGIH			20			

METHANOL

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	130	100	260	200	SKIN
MAK	DEU	130	100	260	200	SKIN
VLA	ESP	266	200			SKIN
VLEP	FRA	260	200			SKIN
TLV	GRC	260	200	325	250	
VLEP	ITA	260	200			SKIN
TGG	NLD	133				SKIN
NDS/NDSch	POL	100		300		SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
ACGIH		262	200	328	250	SKIN

PHENOL

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	8	2	16	4	SKIN 11
VLA	ESP	8	2	16	4	SKIN
VLEP	FRA	7,8	2	15,6	4	SKIN

TLV	GRC	8	2	16	4	
VLEP	ITA	8	2	16	4	SKIN
TGG	NLD	8				SKIN
NDS/NDSch	POL	7,8		16		SKIN
WEL	GBR	7,8	2	16	4	SKIN
OEL	EU	8	2	16	4	SKIN
ACGIH		19,2	5			SKIN

Hexamethyldisiloxane

Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,008	mg/l			
Normal value in marine water				0,0008	mg/l			
Normal value for fresh water sediment				0,065	mg/kg			
Normal value for marine water sediment				0,0065	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				25 mg/kg bw/d				
Inhalation				266 mg/m3				890 mg/m3
Skin								126 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

Ensure good ventilation in the workplace; do not drink, smoke and eat during use.

HAND PROTECTION

None required.

EYE PROTECTION

None required.

SECTION 9. Physical and chemical properties

Properties	Value	Information
Appearance	gel	
Colour	beige	
Odour	characteristic	
Initial boiling point	> 35 °C	
Flash point	< 23 °C	
pH	4 - 4,5	
Density and/or relative density	0,950 - 1,000	

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, on-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

Hexamethyldisiloxane LD50 (Dermal):	> 2000 mg/kg
PHENOL LD50 (Dermal): LD50 (Oral):	660 mg/kg Rat 282 mg/kg Rat
METHANOL LC50 (Inhalation vapours):	> 87,6 mg/l/4h Rat
BENZENE LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):	> 8260 mg/kg Rabbit 3340 mg/kg Rat 43,7 mg/l/4h Rat
TOLUENE	
<u>CARCINOGENICITY</u> LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):	12124 mg/kg Rabbit 5580 mg/kg Rat 28,1 mg/l/4h Rat
TOLUENE	

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Hexamethyldisiloxane LC50 - for Fish	0,46 mg/l/96h
BENZENE LC50 - for Fish	630 mg/l/96h Fish

12.2. Persistence and degradability

PHENOL Rapidly degradable	
METHANOL Solubility in water Rapidly degradable	1000 - 10000 mg/l
BENZENE Solubility in water Rapidly degradable	1000 - 10000 mg/l
TOLUENE Solubility in water Rapidly degradable	100 - 1000 mg/l

12.3. Bioaccumulative potential

PHENOL	
Partition coefficient: n-octanol/water	1,47
METHANOL	
Partition coefficient: n-octanol/water	-0,77
BCF	0,2
BENZENE	
Partition coefficient: n-octanol/water	2,13
BCF	< 10
TOLUENE	
Partition coefficient: n-octanol/water	2,73
BCF	90

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Carc. 1A	Carcinogenicity, category 1A
Muta. 1B	Germ cell mutagenicity, category 1B
Muta. 2	Germ cell mutagenicity, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1

STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H350	May cause cancer.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H361d	Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

Note for users:

The information contained in this document are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.